

PARAMETERS

	Base Station	Beltpack
Interface	2Antenna Interfaces 4-Pin XLR Male DC Input 3.5mm Headset Interface RJ45 Interface 4 wire audio interface USB Type-C Interface Double USB Type-A Interfaces	2Antenna Interfaces 3.5mm Headset Interface 3.5mm TALLY Output Interface USB Type-C Interface
Power Supply Mode	7~36V DC; F970 Battery (Typical)	1600mAh Polymer Lithium Battery
Frequency Response	300Hz to 4KHz	300Hz to 4KHz
Signal to Noise Ratio	> 50dB	> 50dB
Distortion	< 2%	< 2%
Transmission Range	300m Between Beltpack and Base Station	300m Between Beltpack and Base Station
Frequency Bandwidth	CE: 1881.792MHz-1897.344MHz; FCC: 1921.536MHz-1928.448MHz	
Modulation Mode	GFSK	GFSK
Transmission Power	CE:Maximum 21.4dBm FCC: Maximum18.43dBm	CE:Maximum 16.4dBm FCC: Maximum20.61dBm
Receiver Sensitivity	≤ -93dBm	≤ -93dBm
Bandwidth	1.728MHz	1.728MHz
Power Consumption	< 35W	< 6W
Dimension	(L*W*H): 220*170*50mm	(L*W*H): 100*58*22mm
Net Weight	1400g	180g
Temperature Range	0~+40°C(working status) -20~+60°C(storage condition)	0~+40°C(working status) -20~+60°C(storage condition)