

4.0 Resources

4.1 Specifications

INPUTS:

Connector Type	¼" TRS, balanced
THD+N	0.0025%, 1 kHz, unity gain
Max Input Level	+18 dBu, <0.5% THD+N, unity gain
Input Impedance	10 kΩ
Frequency Response	20 Hz - 20 kHz, ±0.5 dB

MONITOR OUTPUT:

Connector Type	¼" TRS, impedance-balanced
THD+N	0.0025%, 1 kHz, unity gain
Max Output Level	+18 dBu, <0.5% THD+N
Output Impedance	51Ω
Frequency Response	20 Hz - 20 kHz, ±0.5 dB

HEADPHONE OUTPUT:

Connector Type	¼" TRS, stereo
Max Output Power	150 mW/Ch, <0.5% THD+N, 60Ω load
Frequency Response	20 Hz - 20 kHz, ±0.5 dB, 60Ω load
Headphone Impedance Working Range	32Ω – 600Ω

POWER:

External Adapter Type	+12 VDC, 1000 mA, center pin positive
-----------------------	---------------------------------------

NOTE: As a commitment to constant improvement, PreSonus Audio Electronics, Inc., reserves the right to change any specification stated herein at any time, without notification.

English

Español

Deutsch

Français